

PATENT ABSTRACTS OF JAPAN

(11) Publication number:

2001015956 A

(43) Date of publication of application: 19.01.2001

(51) Int. Čl

H05K 7/12

(21) Application number:

11186706

(22) Date of filing:

30.06.1999

(54) METHOD FOR DISCONNECTING MOUNTED COMPONENT FROM ENCLOSURE OF ELECTRONIC DEVICE, CONNECTING STRUCTURE, AND ELECTRONIC DEVICE

(57) Abstract:

PROBLEM TO BE SOLVED: To enable a mechanical connecting means which connects a mounted component to an enclosure to cancel the mechanical connection by deforming the connecting means by heating the means by imparting energy to the means from the outside.


SOLUTION: A pair of pawl sections 3 fixed to a mounted component 2 is put in the hole section 4 of the enclosure 1 of an electronic device, and the pawl sections 3 are connected to each other with a spring 5 made of a shape memory alloy. Then the spring 5 is deformed to the memorized shape of the spring 5 by heating the spring 5 to a prescribed temperature by im-

(71) Applicant: NEC CORP

(72) Inventor: OKADA TAKAYUKI

parting energy 6 to the connecting structure from the outside. When the spring 5 is deformed, the spring 3 pulls the pawl sections 3 toward each other in the radial direction of the hole section 4 and disengages the sections 3 from the hole section 4. Therefore, the mounted component 2 can be separated easily from the enclosure 1 in a short time at the time of disassembling or scrapping the electronic device.

COPYRIGHT: (C)2001, JPO



BEST AVAILABLE COPY